



**MARQUIS SERIES • SATIN SERIES
ESPOSED AGGREGATE POOL FINISHES
15 Year Warranty**

Homeowner: _____ Applicator: _____
Address: _____ Address: _____
City, State, Zip: _____ City, State, Zip: _____
Pool Builder: _____ Telephone: () _____
Address: _____
Telephone: () _____ Date Pool Completed: _____
City, State, Zip: _____ Dealer: _____
Batch #: _____ Color: _____

YOU MUST CHECK THE APPROPRIATE PRODUCT BOX

MARQUIS SERIES

SATIN SERIES

Premix-Marbletite Manufacturing Co. (hereinafter referred to as Premix), warrants its product only — Marquis — against failure for fifteen (15) years from the date of installation. In the event of failure, Premix shall, upon verification, provide Marquis materials to repair the area of failure only.

LIMITATIONS:

NOTE: THERE IS NO OTHER WARRANTY OR REPRESENTATION OF ANY KIND, EXPRESS OR IMPLIED (INCLUDING NO WARRANTY OF MERCHANTABILITY OR OF FITNESS) FOR A PARTICULAR PURPOSE.

1. This Warranty **excludes** damage due to defects in workmanship or physical abuse of the pool.
2. Some loss of aggregate is expected, especially in a new installation; this is not to be considered a failure.
3. It is understood that quartz aggregate stone and application techniques will result in variations in tone and appearance. This variation in pool shades is not to be considered a failure. **Marquis** is not guaranteed with regard to color.
4. The contractor shall have the **right to repair the area of failure only**. Marquis material replacement is limited to this repair. It is understood that some cosmetic variation will result.
5. Premix warrants the **Marquis material only and is not responsible for labor to repair said material**.
6. Subsequent costs such as to water replacement, chemicals, land and loss of use of the pool are not covered.
7. This Warranty shall not include pools that have been abused physically or through lack of proper chemical balancing, chlorine applications or other chemical abuses. **SEE REVERSE SIDE POOL CARE INSTRUCTIONS AND ADDITIONAL WARRANTY CONDITIONS.**
8. Minor surfacing checking, cracks and minor cracks are not covered by this warranty.
9. This Warranty is non-transferable.
10. Pool must be checked monthly by a pool retail outlet having water testing capabilities. Computerized records must be present at time of inspection.

The Premix warranty is not valid unless this document is completed in full and returned to Premix within thirty (30) days of installation of the Marquis material. **WARRANTY MUST BE SENT BY CERTIFIED MAIL!** Purchaser must retain returned receipt.

**Attn: Warranty Department
Premix-Marbletite Manufacturing Co. • 1259 N.W. 21st. Street • Pompano Beach, FL 33069
954.917.7665**

WHITE: PREMIX YELLOW: CONTRACTOR PINK: HOMEOWNER

POOL WATER CHEMISTRY

It is necessary for the longevity of your pool finish and as a condition of this warranty, that the following chemical guidelines and **Sequestering Agent**® levels must be followed and maintained: Sanitizer levels must be maintained in accordance with the manufacture's specifications of the sanitizer you are using. (Example: Free Chlorine = 1 - 3ppm)

pH	7.2 - 7.6
Total Alkalinity (TA)	80 - 120 ppm
Calcium Hardness (CH)	200 - 400 ppm
Cyanuric Acid	40 - 60 ppm
Sequestering Agent	10 - 12 ppm (6oz. Per 10,000 gal of water)
Salt Water pools	Lower pH to 7.2 weekly (Very Important) Use Sequestering Agent for salt water pools

Pool fill water containing high levels of metals may need to be pre-treated and filtered before being added to your pool. **DO NOT** stop the water while the pool is filling. If adding additional fill hoses, add to the deep end of the pool only. The initial process, including start up chemicals, should be done by a pool professional. This may take several days. Afterwards balance the pool water to the above noted water parameters. **Check** the pH several times per week for the first few weeks and add pool acid **pre-diluted** to the deep end of the pool to lower the pH to 7.0-7.2 range or lower if needed. **Never** allow the pH to rise above 7.6 during the first 30 days. Brush the pool daily for the first 30 days, then as needed. To help prevent metal stains and scaling of the finish and to up-hold your product warranty, you must add the proper amount of Sequa-Sol® or any leading brand of Sequestering Agent weekly. (Noted above) After the first 30 days, check the pool water routinely at least once a week or more often and keep the water balanced to the above noted water chemistry parameters. For Salt water pools: do not add salt to the pool for the first 30 days. **Be sure** to add pool acid **weekly** and lower the pH to 7.2 ppm. No pool cleaners without brushes or vacuums with wheels for the first 30 days. **Do not** add Calcium for the first 60 days; then only if it is below 200 ppm.

WARRANTY CLAIM PROCEDURES

To initiate a warranty claim, notify Premix-Marbletite Mfg. Co. , 3790 Park Central Boulevard North, Pompano Beach, FL 33064. Prior to an inspection, Premix-Marbletite Mfg. Co. must receive by certified mail a brief not describing the complaint and photocopies (do not send the originals) of the following:

- (1) Warranty as completed at time of application
- (2) Original "return receipt" as completed at time of application.
- (3) Historical copies of weekly (or more frequent) results of pool water chemistry test results.