



## ADICOTE

*a bonding agent & fill coating for interior & exterior use for cementitious substrates*

---

### DESCRIPTION

Adicote is a polyvinyl acetate-based adhesive designed for use as a bonding agent and fill coating for interior or exterior substrates of concrete masonry and stucco.

Adicote is non-toxic and resistant to most mild acids. It has the capability of bonding any two cementitious materials.

### ADVANTAGES

Adicote provides:

- Reduced shrinkage and cracking
- Even suction of the surface to which stucco or plaster are to be applied
- Pure white to eliminate bleeding

### LIMITATIONS

Do not apply in temperatures lower than 50°F or if temperatures are expected to fall below 40°F within 48 hours. Not recommended for pre-painted surfaces. Do Not dilute product.

### COMPOSITION AND MATERIALS

Polyvinyl acetate-based resin: This material is factory prepared and delivered to the job as herein before specified.

The components shall be:

- A.) The vinyl polymer has a stable dispersion of saturated vinyl polymer resin particles in water prepared by emulsion polymerization and suitably modified by a plasticizing Co-monomer.
- B.) Intrinsic viscosity prepared to factory standards.
- C.) Residual monomer content - 0.5% or less.
- D.) Average particle size -0.1 micron to 1.0 micron.
- E.) The resin, without the addition of any mono-polymerizable plasticizing ingredient, shall show no evidence of cracking, chipping or flaking when a 30.3 mils dry film, aged 7 days at 120 degrees F or forced dried at 130 degrees C for 1/2 hour (after a 2 hour air dry at room temperature) is allowed to cool to 73°F at 50% relative humidity and then bent over a 1/8" mandrel in accordance with method 622.1 of Federal Specifications TTP-141.

### INSTALLATION

#### Surface Preparation

Concrete masonry and stucco surfaces shall be prepared by removing all dust, oil, grease stains and any other foreign materials that may inhibit adhesive.

The temperature of the surface and of the atmosphere shall not be less than 50°F during application.

Base coats should be allowed adequate time to cure. When surfaces are glossy, they should be roughened to allow for a more absorbent surface.

### MIXING

Stir briskly prior to use

### APPLICATION

Adicote is usually applied by spray, brush or paint roller in a one coat application. Protect Adicote during drying from debris and other foreign matter. Do not allow any water to penetrate behind Adicote. Cementitious products can be applied while Adicote is in a tacky condition approximately 45 minutes after application or later.

### NOTE

Any fill coating that has been allowed to stand in the open for more than 8 hours or longer shall be discarded. Apply another fill coating to such surfaces with a stiff brush having Tampico or Palmyra bristles no longer than 2-1/2 inches and a scrub and work thoroughly into the surface to seal all pores and voids.

### AVAILABILITY/COVERAGE

Adicote is available in 1, 5 and 55 gallon containers.

Per gallon coverage varies with the type of job, etc. Guideline estimate for coverage 200 - 300 Sq. Ft. per gallon.



## **ADICOTE**

*a bonding agent & fill coating for interior & exterior use for cementitious substrates*

---

### **LIMITED WARRANTY**

The product shall be in its unopened package, of the kind specified within. There is no other warranty or representation of any kind, express or implied (including no warranty of merchantability or of fitness for a particular purpose). No warranty shall be implied by law.

This Limited Warranty continues only until such time as the buyer opens the package and examines its contents.

If the buyer, after opening the package and examining its contents, determines that the product is not of the kind specified herein, the buyer should write to Premix-Marbletite Manufacturing Company, 1259 N.W. 21st Street, Pompano Beach, Florida 33069 explaining the defect and enclosing a sample of the product. Premix-Marbletite, upon receipt of the sample from the buyer and without cost to the buyer, will replace the portion of the product that is determined to be defective. This shall be the buyer's sole remedy for breach of warranty and such remedy shall be in lieu of any claim for damages, including consequential damages.

Some States do not allow limitations on how long an implied warranty lasts, or exclusions or limitations of incidental or consequential damages, so the above limitations or exclusions may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from State to State.

### **TECHNICAL SERVICES**

Factory trained, experienced representatives are available to answer questions and assist with recommendations.

**PREMIX-MARBLETITE MFG. CO.**

**1259 NW 21st STREET • POMPANO BEACH, FL. 33069**  
**954/917.7665 • fx: 954/917.2775 • 800/432.5097**

**PREMIX-MARBLETITE MFG. CO.**

**325 OLD SANFORD OVIEDO ROAD • WINTER SPRINGS, FL. 32708**  
**407/327.0830 • fx: 407/327.8942 • 800/432.5097**