



SureBond

SureBond is a two component, factory blended mixture of liquid resin and modified cement — aggregates and various admixtures — specifically designed as a bond or scratch coat.

USES

SureBond's chemical properties make it the product of choice for pool, patio, deck or sidewalk renovation. It provides superior performance as a bond coat over existing cementitious surfaces. The finish coat locks to the **SureBond** both chemically and mechanically to reduce the possibility of bond loss, thereby reducing the need for strong acid washing, sand blasting or axing of the existing surface.

FEATURES & BENEFITS

- Superior bonding with most cementitious surfaces
- Superior elongation that allows for minor movement of substrates

COVERAGE

SureBond is packaged as a unit — [2] 65lb. Bags and a 5 gallon bucket of liquid resin, yielding a coverage of 600 - 800 square feet.

SURFACE PREPARATION

Patch, level or resurface as required to provide a smooth substrate. Surface must be clean, cool, dry and free of mold, mildew, fungus, algae, dirt, grease, paint, efflorescence or other foreign matter that may prevent or inhibit proper bonding.

NOTE: Only the experienced applicator can make the decisions as to what surface preparation may be required.

- 1.] On previously plastered pools it is necessary to grind around the tile, lights, returns, etc., to allow for a smooth transition.
- 2.] On previously painted pools, the surface must be sandblasted to remove the old paint completely.
- 3.] Thoroughly wash the surface with a TSP solution to remove body oils and suntan lotions. Acid wash with a 50/50 solution of muriatic acid and water, rinse with a neutralized solution of baking soda and water, then finally rinse with clean water.

MIXING

Measuring equal amounts of water and mixing for equal amounts of time from batch to batch will ensure product consistency from batch to batch. **SureBond** will require approximately 2½ - 3 gallons of portable water per bag. Start the mixing process by adding 2/3 of the total required water to the mixer. Add the appropriate amount of **SureBond** and then add the remaining 1/3 of the required water. Mix for approximately 5 minutes to bring the material to a workable consistency. Allow the mix to set for 5



minutes, then remix and add additional water if necessary to achieve the desired workable consistency. Do not retemper the mix after this.

APPLICATION

Apply the **SureBond** with a 1¼" nap roller. Let the application set for 5 minutes then double back with a damp roller to create a rough surface texture.

Allow **SureBond** to thoroughly dry for a minimum of 2a4 hrs. Before coating. If temperatures are below 50°F or wet conditions such as fog, high humidity or rain exists, the drying times will be significantly extended.

CLEAN UP

Clean all tools and equipment with water while still wet. Cured material can be removed mechanically or chemically.

STORAGE

Turn inventory regularly and keep bagged product protected from all forms of moisture, both direct and indirect, to assure maximum product usage, uniformity and productivity.

LIMITATIONS

Apply only when surface and ambient temperatures are 50°F - 100°F and relative humidity is below 85% throughout the application and for a minimum of 24 hours thereafter or prior to replastering. Protect **SureBond** from rain, fog or other moisture after application. Moisture will prevent **SureBond** from curing. Surface hardness of **SureBond** is not an indication of complete cure.

WARRANTY

The effectiveness of this product depends upon its proper application and the condition and preparation of the surface to which it is applied.

Limited Warranty: The product shall be in its unopened package and of the kind specified within. There is no other warranty or representation of any kind, express or implied (including no warranty of merchantability or of fitness for a particular purpose). No warranty shall be implied by law. This limited warranty continues only until such time as the buyer opens the package and examines its contents. If the buyer, after opening the package and examining its contents, determines that the product is not the kind specified herein, the buyer should write to **Premix-Marbletite Manufacturing Company, 1259 NW 21st St., Pompano Beach, FL 33069**, explaining the defect and enclosing a sample of the product. **Premix-Marbletite**, upon receipt of the sample from the buyer, will replace the portion of the product that is determined to be defective. This shall be the buyer's sole remedy to breach of warranty and such remedy shall be in lieu of any claim for damages, including consequential damages.